



- GENERAL NOTES:**
- ALL AXLES AND SHAFTS ARE CHROME PLATED.
 - ALL ROLLERS AND PIVOT POINTS ARE EQUIPPED WITH TEFLON SELF-LUBRICATING BEARINGS.
 - INSTALLER TO FURNISH APPROX. 10 GALLONS OF A MULTI-VISCOSITY ISO-68 GROUP 1 BASE OIL & 5' EXTRA HEAVY, DOUBLE WIRE BRAID HOSE (SAE 100R2) OR EXTRA HEAVY SEAMLESS PIPING FROM THE POWER UNIT TO THE EQUIPMENT WITH 5" JIC FEMALE FITTING ON THE ENDS.
 - REINFORCE CONCRETE TO SUIT LOCAL SOIL CONDITIONS PLUS YOUR DESIRED SAFETY FACTORS.
 - OVERALL POWER UNIT SIZE: 26" WIDE X 22" LONG X 21" HIGH (INCLUDING MOTOR, AND BRACKETS FOR WALL MOUNTING).
 - CONCRETE WORK, REINFORCING, BUILDING MODIFICATIONS, RESERVOIR FLUID, PIPING, ELECTRICAL WIRING, IMBEDDED ITEMS, INSTALLATION, ETC. (BY OTHERS)
 - ADVANCE LIFTS, INC. TO SUPPLY:
 - (1) 20' LG. PUSHBUTTON CORD.
 - (2) 20' LENGTH OF 25 O.D. CLEAR POLYURETHANE TUBING FOR THE VENT LINES.
 - FINISH: BLUE PAINT

- SPECIFICATIONS:**
- CAPACITY : 8,000 LBS MAX. LIFTING CAPACITY
6,500 LBS MAX. AXLE CAPACITY ENDS
5,000 LBS MAX. AXLE CAPACITY SIDES
- PLATFORM : 72" X 96"
SAFETY TREAD DECK,
REMOVABLE HANDRAILS - STEEL
12" X 72" STEEL BRIDGE WITH CHAIN
BEVEL TOE GUARDS
SAFETY STRIPING
- SPEED : 10 FPM
- TRAVEL : 58" (FROM A 15" LOWERED HEIGHT)
- LOWERED HEIGHT : 15"
- POWER UNIT : 5 HP MOTOR 230 V 60 Hz 3PH
(REMOTE FROM LIFT)
- CONTROL : UP-DOWN WEATHER-PROOF PUSH-BUTTON
STATION, PENDANT TYPE NEMA 1, 3, 3R, 4, 4X.

IN NEMA 12 ENCLOSURE : MAGNETIC STARTER, W/ OVERLOAD
230 V TO 24 V CONTROL TRANSFORMER.

APPROXIMATE SHIPPING WEIGHT: #4200

DO NOT SCALE DRAWING

ADVANCE LIFTS		Advance Lifts, Inc. 701 S. Kiss Rd. St. Charles, IL 60174 Phone: 630-584-8811 Fax: 630-584-8405	
JOB NAME	X	REV	DATE
JOB NUMBER	X		
SCALE	1" = 1'-0"		
DATE	X		
DRN	X		
APP'D			
TITLE	SUPERDOK MODEL 3200	NO.	D-