



- GENERAL NOTES:**
- ALL AXLES AND SHOOTS ARE CHROME PLATED.
 - ALL ROLLERS AND PIVOT POINTS ARE EQUIPPED WITH TEFLON SELF-LUBRICATING BEARINGS.
 - POWER UNIT EQUIPPED WITH ONE PIECE "ADVANCE FLOW" VALVE MANIFOLD.
 - INSTALLER TO FURNISH APPROX. 10 GALLONS OF A MULTI VISCOSITY ISO-46 GROUP II BASE OIL & (1) 20' LG. 5" EXTRA HEAVY, DOUBLE WIRE BRAID HOSE (SAE 100R2) OR EXTRA HEAVY SEAMLESS PIPING FROM THE POWER UNIT TO THE EQUIPMENT WITH 5" JIC FEMALE FITTING ON THE ENDS.
 - REINFORCE CONCRETE TO SUIT LOCAL SOIL CONDITIONS PLUS YOUR DESIRED SAFETY FACTORS.
 - OVERALL POWER UNIT SIZE: 26" WIDE X 22" LONG X 21" HIGH (INCLUDING MOTOR, AND BRACKETS FOR WALL MOUNTING).
 - CONCRETE WORK, REINFORCING, BUILDING MODIFICATIONS, PIPING, RESERVOIR FLUID, ELECTRICAL WIRING, IMBEDDED ITEMS, INSTALLATION, ETC. (BY OTHERS).
 - ADVANCE LIFTS, INC. TO SUPPLY: (1) 20' LG. PUSHBUTTON CORD.
 - FINISH:

- SPECIFICATIONS:**
- CAPACITY: 8,000 LBS MAX. LIFTING CAPACITY
6,500 LBS MAX. AXLE CAPACITY ENDS
5,000 LBS MAX. AXLE CAPACITY SIDES
- PLATFORM: 84" X 120", SAFETY TREAD DECK, REMOVABLE HANDRAILS - STEEL, 12" X 72" STEEL BRIDGE WITH CHAIN BEVEL TOE GUARDS, SAFETY STRIPING
- SPEED: 10 FPM
- TRAVEL: 58" (FROM A 15" LOWERED HEIGHT)
- LOWERED HEIGHT: 15"
- POWER UNIT: 5 HP MOTOR 230 V 60 Hz 3PH (REMOTE FROM LIFT)
- CONTROL: UP/DOWN WEATHER-PROOF PUSHBUTTON STATION, PENDANT TYPE NEMA 1, 3, 3R, 4, 4X.
- IN NEMA 12 ENCLOSURE: MAGNETIC STARTER, W/ OVERLOAD 230 V TO 24 V CONTROL TRANSFORMER.
- APPROXIMATE SHIPPING WEIGHT: 4,750

DO NOT SCALE DRAWING

ADVANCE LIFTS		Advance Lifts, Inc. 701 E. Kirk Rd. St. Charles, IL 60174 Phone: 630-684-9881 Fax: 630-584-9405	
JOB NUMBER	X	REVISED	BY DATE
SCALE	CAD		
DRN	X	CD	
BY			
TITLE	SUPERDOK MODEL 3250	NO.	D-