



- GENERAL NOTES:**
- ALL AXLES AND SHAFTS ARE CHROME PLATED.
 - ALL ROLLERS AND PIVOT POINTS ARE EQUIPPED WITH TEFLON SELF-LUBRICATING BEARINGS.
 - INSTALLER TO FURNISH APPROX. 10 GALLONS OF A MULTI-VISCOUSITY ISO-46 GROUP II BASE OIL, 5' EXTRA HEAVY, DOUBLE WIRE BRAID HOSE (GAE 100R2A) OR EXTRA HEAVY SEAMLESS PIPING FROM THE POWER UNIT TO THE EQUIPMENT WITH .5" JIC FEMALE FITTING ON THE ENDS.
 - REINFORCE CONCRETE TO SUIT LOCAL SOIL CONDITIONS PLUS YOUR DESIRED SAFETY FACTORS.
 - OVERALL POWER UNIT SIZE: 28" WIDE X 22" LONG X 21" HIGH (INCLUDING MOTOR, AND BRACKETS FOR WALL MOUNTING).
 - CONCRETE WORK, REINFORCING, BUILDING MODIFICATIONS, RESERVOIR FLUID, PIPING, ELECTRICAL WIRING, IMBEDDED ITEMS, INSTALLATION, ETC. (BY OTHERS)
 - ADVANCE LIFTS, INC. TO SUPPLY: (1) 28" LG. PUSHBUTTON CORD, -20' LENGTH OF .25 O.D. CLEAR POLYURETHANE TUBING FOR THE VENT LINES.
 - FINISH: BLUE PAINT
 - PIT DIMENSION TOLERANCES ARE PLUS .25", MINUS 0" (+.25", -0").

- SPECIFICATIONS:**
- CAPACITY:** 10,000 LBS MAX. LIFTING CAPACITY
7,500 LBS MAX. AXLE CAPACITY ENDS
5,000 LBS MAX. AXLE CAPACITY SIDES
- PLATFORM:** 72" X 96" SAFETY TREAD DECK, REMOVABLE HANDRAILS - STEEL
12" X 72" STEEL BRIDGE WITH CHAIN BEVEL TOE GUARDS
SAFETY STRIPING
- SPEED:** 8 FPM
- TRAVEL:** 58" (FROM A 15" LOWERED HEIGHT)
- LOWERED HEIGHT:** 15"
- POWER UNIT:** 5 HP MOTOR 230 V 60 Hz 3PH (REMOTE FROM LIFT)
- CONTROL:** UP-DOWN WEATHER-PROOF PUSHBUTTON STATION, PENDANT TYPE NEMA 1, 3, 3R, 4, 4X.
- IN NEMA 12 ENCLOSURE:** MAGNETIC STARTER, W/ OVERLOAD 230 V TO 24 V CONTROL TRANSFORMER.
- APPROXIMATE SHIPPING WEIGHT:** #4525

NO NET SCALE DRAWING

ADVANCE LIFTS Advance Lifts, Inc. 701 S. KVA Rd.
St. Charles, IL 60174
Phone: 630-584-9887 Fax: 630-584-9405

JOB NAME: X

JOB NUMBER: X

SCALE: X

REV	DATE	BY	REVISIONS
001			
002			
003			

TITLE: SUPERDOK MODEL 3300

NO. D- REV.