



**GENERAL NOTES:**

- ALL AXLES AND SHAFTS ARE CHROME PLATED.
- ALL ROLLERS AND PIVOT POINTS ARE EQUIPPED WITH TEFLON SELF-LUBRICATING BEARINGS.
- INSTALLER TO FURNISH APPROX. 5 GALLONS OF A MULTI-VISCOSITY ISO-46 GROUP II BASE OIL & 5' EXTRA HEAVY DOUBLE WIRE BRAID HOSE (SAE 100RAN OR EXTRA HEAVY SEAMLESS PIPING FROM THE POWER UNIT TO THE EQUIPMENT WITH 5" JIC FEMALE FITTING ON THE ENDS.
- REINFORCE CONCRETE TO SUIT LOCAL SOIL CONDITIONS PLUS YOUR DESIRED SAFETY FACTORS.
- OVERALL POWER UNIT SIZE: 20" WIDE X 22" LONG X 21" HIGH (INCLUDING MOTOR, AND BRACKETS FOR WALL MOUNTING).
- CONCRETE WORK, REINFORCING, BUILDING MODIFICATIONS, RESERVOIR FLUID, PIPING, ELECTRICAL WIRING, IMBEDDED ITEMS, INSTALLATION, ETC. (BY OTHERS).
- ADVANCE LIFTS, INC. TO SUPPLY:
  - (1) 20' LG. PUSHBUTTON CORD.
  - (2) LENGTH OF .25 O.D. CLEAR POLYURETHANE TUBING FOR THE VENT LINES.
- FINISH: BLUE PAINT
- PIT DIMENSION TOLERANCES ARE PLUS .25", MINUS 0" (+.25", -0").

**SPECIFICATIONS:**

CAPACITY: 10,000 LBS MAX. LIFTING CAPACITY  
7,500 LBS MAX. AXLE CAPACITY ENDS  
5,000 LBS MAX. AXLE CAPACITY SIDES

PLATFORM: 72" X 120", SAFETY TREAD DECK, REMOVABLE HANDRAILS - STEEL, 12" X 72" STEEL BRIDGE WITH CHAIN BEVEL TOE GUARDS, SAFETY STRIPING

SPEED: 8 FPM

TRAVEL: 58" (FROM A 15" LOWERED HEIGHT)

LOWERED HEIGHT: 15"

POWER UNIT: 5 HP MOTOR 230 V 60 Hz 3PH (REMOTE FROM LIFT)

CONTROL: UP-DOWN WEATHER-PROOF PUSHBUTTON STATION, PENDANT TYPE NEMA 1, 3, 3R, 4, 4X.

IN NEMA 12 ENCLOSURE: MAGNETIC STARTER, W/ OVERLOAD 230 V TO 24 V CONTROL TRANSFORMER.

APPROXIMATE SHIPPING WEIGHT: #4,885

80 NOT SCALE DRAWING

<b>ADVANCE LIFTS</b>		Advance Lifts, Inc. 701 E. Kirk Rd. St. Charles, IL 60174 Phone: 630.684.9881 Fax: 630.584.9405	
JOB NUMBER	X	REVISED	BY DATE
SCALE	CAD		
DRAWN BY	X	DATE	
CHECKED BY	CD		
BY			
TITLE	SUPERDOK MODEL 3320	NO.	D-