



- GENERAL NOTES:**
- ALL AXLES AND SHAFTS ARE CHROME PLATED.
 - ALL ROLLERS AND PIVOT POINTS ARE EQUIPPED WITH TEFLON SELF-LUBRICATING BEARINGS.
 - INSTALLER TO FURNISH APPROX. 10 GALLONS OF A MULTI-VISCOSITY ISO-68 GROUP 1 BASE OIL & 1\"/>

- REINFORCE CONCRETE TO SUIT LOCAL SOIL CONDITIONS PLUS YOUR DESIRED SAFETY FACTORS.
- OVERALL POWER UNIT SIZE: 26\"/>

SPECIFICATIONS:

CAPACITY : 10,000 LBS MAX. LIFTING CAPACITY
7,500 LBS MAX. AXLE CAPACITY ENDS
5,000 LBS MAX. AXLE CAPACITY SIDES

PLATFORM : 84\"/>

SPEED : 8 FPM

TRAVEL : 58\"/>

APPROXIMATE SHIPPING WEIGHT: 44,765

DO NOT SCALE DRAWING

ADVANCE LIFTS		Advance Lifts, Inc. 701 S. Kim Rd. St. Charles, IL 60174 Phone: 630-584-8811 Fax: 630-584-8405	
JOB NAME	X	JOB NUMBER	1431004
SCALE	CAD	DATE	
REV	X	BY	
BY	X	DATE	
APP'D		REV	
TITLE: SUPERDOK MODEL 3330		NO.	D-