



GENERAL NOTES:

1. ALL AXLES AND SHAFTS ARE CHROME PLATED.
2. ALL ROLLERS AND PIVOT POINTS ARE EQUIPPED WITH TEFLON SELF-LUBRICATING BEARINGS.
3. INSTALLER TO FURNISH APPROX. 15 GALLONS OF A MULTI-VISCOSITY ISO-46 GROUP II BASE OIL & (2) 20' 5\"/>

SPECIFICATIONS:

- CAPACITY :** 20,000 LBS MAX. LIFTING CAPACITY
16,000 LBS MAX. AXLE CAPACITY ENDS
14,000 LBS MAX. AXLE CAPACITY SIDES
- PLATFORM :** 96" X 144",
SAFETY TREAD DECK,
REMOVABLE HANDRAILS - STEEL
12" X 72" STEEL BRIDGE WITH CHAIN
BEVEL TOE GUARDS
SAFETY STRIPPING
- SPEED :** 8 FPM
- TRAVEL :** 58" (FROM A 20" LOWERED HEIGHT)
- LOWERED HEIGHT :** 20"
- POWER UNIT :** 7.5 HP MOTOR 230 V 60 Hz 3PH
(REMOTE FROM LIFT)
- CONTROL :** UP-DOWN WEATHER-PROOF PUSHBUTTON
STATION, PENDANT TYPE NEMA 1, 3, 3R, 4, 4X.
- IN NEMA 12 ENCLOSURE :** MAGNETIC STARTER, W/ OVERLOAD
230 V TO 24 V CONTROL TRANSFORMER,

APPROXIMATE SHIPPING WEIGHT: #8,100

ADVANCE LIFTS

Address: Advance Lifts, Inc. 701 S. RIA RD.
St. Charles, IL 60174
Phone: 630-584-8851 Fax: 630-584-9426

JOB NAME: X

JOB NUMBER: X

SCALE: 1/4" = 1'-0"

DATE: X

BY: X

REVISED: X

FILE: SUPERDOX MODEL 4480