



- GENERAL NOTES:**
1. ALL AXLES AND SHAFTS ARE CHROME PLATED.
 2. ALL ROLLERS AND PIVOT POINTS ARE EQUIPPED WITH TEFLON SELF-LUBRICATING BEARINGS.
 3. 3" VERTICAL AND 4" HORIZONTAL TOE CLEARANCE SIDES.
 4. ADVANCE LIFTS, INC. TO SUPPLY:
- (1) PREWIRED 18' LG. POWER CORD (FROM LIFT BASE TO SUPPLY).
 5. FINISH BLUE PAINT

- SPECIFICATIONS:**
- CAPACITY : 5,500 LBS MAX. LIFTING CAPACITY
2,750 LBS MAX. AXLE CAPACITY ENDS
- PLATFORM : 72" X 96" SAFETY TREAD DECK
REMOVABLE HANDRAILS - STEEL
18' X 60" STEEL HINGED BRIDGE WITH CHAIN
30' X 60" CHECK RAMP- STEEL
61.5" BETWEEN HANDRAILS (PLATFORM WIDTH)
SAFETY CHAINS
- SPEED : 13 FPM
- TRAVEL : 53" (FROM A 5' LOWERED HEIGHT)
- LOWERED HEIGHT : 5'
- POWER UNIT : 5 HP MOTOR, 230V 60Hz 3PH
SELF CONTAINED AND PRE-WIRED
- CONTROLS : UP-DOWN WEATHER-PROOF PUSHBUTTON STATION
ON CORD (PENDANT TYPE NEMA 1, 3, 5E, 4, 4C,
IN NEMA 12 ENCLOSURE - MAGNETIC STARTER, W/ OVERLOAD
230V TO 24 V CONTROL TRANSFORMER.
- VOLTAGE 230V / 3PH
ADVANCE TO SUPPLY NEMA L15-20P PLUG
CUSTOMER TO SUPPLY NEMA L15-20R RECEPTACLE
- APPROXIMATE SHIPPING WEIGHT: 42,290
- ALL DIMENSIONS ARE GIVEN IN INCHES UNLESS OTHERWISE NOTED.

DIMENSIONS ARE GIVEN IN INCHES UNLESS NOTED OTHERWISE
DO NOT SCALE DRAWING

ADVANCE LIFTS Advance Lifts, Inc. Phone: 630-584-9881
701 S. Oak Road St. Charles, IL 60174 Fax: 630-584-6637

REV	DESCRIPTION	DATE	BY	CHKD
2290	N.T.S.			
DATE TO BE SHIPPED	BY			
BY				
ANGULAR				
SPECIES				
INSTANT DOCK MODEL 6568		QTY	REV	