



- GENERAL NOTES:**
- ALL AXLES AND SHAFTS ARE CHROME PLATED.
 - ALL ROLLERS AND PIVOT POINTS ARE EQUIPPED WITH TEFLON SELF-LUBRICATING BEARINGS.
 - ADVANCE LIFTS, INC. TO SUPPLY 10 GALLONS OF A MULTI VISCOSITY ISO-46 GROUP II BASE OIL & (1) 20' 5" EXTRA HEAVY DOUBLE WIRE BRAID HOSE (SAE 100R2) FOR THE POWER UNIT TO THE EQUIPMENT CONNECTION WITH 5" JIC FEMALE FITTINGS ON THE ENDS.
 - REINFORCE CONCRETE TO SUIT LOCAL SOIL CONDITIONS PLUS YOUR DESIRED SAFETY FACTORS.
 - OVERALL POWER UNIT SIZE: 26" WIDE X 22" LONG X 21" HIGH (INCLUDING MOTOR, AND BRACKETS FOR WALL MOUNTING).
 - CONCRETE WORK, REINFORCING, BUILDING MODIFICATIONS, PIPING, ELECTRICAL WIRING, EMBEDDED ITEMS, INSTALLATION, ETC. (BY OTHERS)
 - ADVANCE LIFTS, INC. TO SUPPLY:
 - (1) 20' LG. PUSHBUTTON CORD.
 - 20' LENGTH OF 25 O.D. CLEAR POLYURETHANE TUBING FOR THE VENT LINES.
 - ELECTRIC TOE GUARDS.
 - (2) HYDRAULIC VELOCITY FUSES IN THE HYDRAULIC SYSTEM.
 - FINISH: BLUE PAINT
 - PIT DIMENSION TOLERANCES ARE PLUS .25", MINUS 0" (+.25", -0").

SPECIFICATIONS:

CAPACITY: 8,000 LBS MAX. LIFTING
6,500 LBS MAX. AXLE CAPACITY ENDS
5,000 LBS MAX. AXLE CAPACITY SIDES

PLATFORM: 96" X 96"
SAFETY TREAD DECK
REMOVABLE HANDRAILS - STEEL
12" X 72" STEEL BRIDGE WITH CHAIN BEVEL TOE GUARDS
SAFETY STRIPPING

SPEED: 10 FPM

TRAVEL: 58" (FROM A 15" LOWERED HEIGHT)

LOWERED HEIGHT: 15"

POWER UNIT: 5 HP MOTOR 230 V 60 HZ 3 PH
(REMOTE FROM LIFT)

CONTROL: UP - DOWN WEATHERPROOF PUSHBUTTON
STATION, PENDANT TYPE NEMA 1, 3, 3R, 4, 4X.

IN NEMA 12 ENCLOSURE: MAGNETIC STARTER, W/ OVERLOAD
230 V TO 24 V CONTROL TRANSFORMER.

APPROXIMATE SHIPPING WEIGHT: #4,600

ADVANCE LIFTS		Advance Lifts, Inc. 701 S. King Rd. St. Charles, IL 60174 Phone: 630-584-9881 Fax: 630-584-9405	
JOB NAME: BUCKHEAD CHURCH "A"			
JOB NUMBER: SET73	DATE: 5/15/06	SCALE: CAD	REV: 01
DRAWN: GCJ	CHECKED: [Signature]	DATE: [Blank]	BY: [Blank]
PROJECT: SUPERDOK MODEL 3280	TITLE: SUPERDOK MODEL 3280	NO.:	REV: D-15456