

ADVANCE LIFTS



Pallet Muncher



Drum Crusher

RECYCLING EQUIPMENT

WHY USE AN ADVANCE DRUM CR

Get rid of unsightly metal drums and wooden pallet clutter that takes up valuable floor space and creates a potential fire and safety hazard. The drum crusher safely reduces drums to 4" slugs in approximately 43 seconds. The Pallet Muncher chews up pallets up to 48" x 54" at the rate of 5–8 an hour depending on the pallet, and at 1/3 the cost of a traditional pallet shredder.

DRUM CRUSHER

Usage And Operation

The Drum Crusher is intended for indoor use only. You simply load the drum, close the door and press the down button. The cycle is automatic. When the drum is crushed, the cylinder returns to the retracted position. For safety, all cylinder movement stops whenever the door is opened or the emergency stop button is pressed.



Model No.	Horse-power	Cycle Time (sec.)	Chamber Size (In.)	Overall Size (In.)	Platen Force (lbs.)	Cylinder Bore x Stroke (In.)	Cylinder Rod Size (In.)	Approx. Volume Reduction	Shipping Weight (Lbs.)
ADC-6000	7.5	43	30 x 30 x 36-3/4	36 x 39 x 104	60,000	6 x 34	4	8 to 1	2400
ADC-6100	7.5	43	30 x 30 x 39	36 x 39 x 107	60,000	6 x 37	4	8 to 1	2700
ADC-6200*	7.5	43	30 x 30 x 36-3/4	36 x 39 x 104	60,000	6 x 34	4	8 to 1	2400


* In-Drum Compactor Model

Standard Voltage 230/60/3. Oil Heater, Remote Power Unit And Fork Pockets Available.

CRUSHER OR PALLET MUNCHER?

PALLET MUNCHER

Usage And Operation



The Muncher teeth are operated by reciprocating hydraulic cylinders

The Advance Pallet Muncher can be operated indoors or, with its optional weatherproof power unit cover, it can be operated outdoors. With its standard power unit the Pallet Muncher can be operated continuously for 2.5 hours. From that point onward, due to possible heat build up, it can be operated approximately 20 minutes per hour. Add the optional continuous duty power unit, with its heat

exchanger, and there are no restrictions on time of use. To operate, lower the pallet chute, place a pallet on the tray making sure the pallet stringers are perpendicular to the teeth shafts, raise the pallet chute, engage the chute locking lever, set the shutoff timer. The Pallet Muncher is designed for stringer pallets; it is not designed for block pallets.



Chip hopper not included.

Model	Capacity (In.)	Horsepower	Overall Size (In.)	Shipping Weight (Lbs.)
APM-4854	48 x 54 Pallets	10	78 x 60 115	5500

Standard Voltage 230/60/3. Optional Weatherproof Power Unit Cover And Heat Exchanger Available.

THE ADVANCE ADVANTAGE

- UL approved electrical assemblies.
- Advance industrial grade cylinders.
- Oven baked-on paint finish.
- 8 standard colors to choose from.
- Chrome plated axles and shafts.
- Drum Crusher has 2" thick platen and bottom plate.
- Drum Crusher Factory Mutual approved safety door latch allows the door to be opened from inside the chamber.
- Pallet Muncher's counter balanced loading chute and positive safety locking lever provides safety and ease of operation.



Optional weatherproof power unit cover (shown without electrical panel cover).



Optional heat exchanger.



Advance Lifts Parts & Labor Warranty

For a period of ONE YEAR from date of shipment from Company's plant, the Company agrees to replace or repair, free of charge, any defective parts, material or workmanship on new equipment. This shall include electrical and hydraulic components.

Company authorization must be obtained prior to the commencement of any work. The Company reserves the right of choice between effecting repairs in the field or paying all freight charges and effecting the repairs at the Company's plant. The Company further reserves the right of final determination in all warranty considerations. Evidence of overloading, abuse or field modification of units without Company approval shall void this warranty. No contingent liabilities accepted.



701 Kirk Road, St. Charles, IL 60174
1-800-843-3625
fax 630-584-9405

www.advancelifts.com

APM/3/01