

SPECIFICATIONS:

CAPACITY: 12,000 LBS MAX. LIFTING CAPACITY 9,600 LBS MAX. AXLE CAPACITY ENDS 8,400 LBS MAX. AXLE CAPACITY SIDES

PLATFORM : 96" WIDE X 132" LONG SAFETY TREAD DECK REMOVABLE STEEL GUARDRAILS 12" LONG X 72" WIDE HINGED STEEL BRIDGE ALL WITH CHAINS BEVEL TOE GUARDS SAFETY STRIPING

SPEED: 7 FPM

TRAVEL: 58" (FROM A 15" LOWERED HEIGHT)

LOWERED HEIGHT: 15"

POWER UNIT : 5 HP MOTOR 230V 60 Hz 3PH (REMOTE FROM LIFT)

CONTROL: UP-DOWN WEATHER-PROOF PUSHBUTTON STATION, PENDANT TYPE NEMA 1, 3, 3R, 4, 4X.

IN NEMA 12 ENCLOSURE : MAGNETIC STARTER, W/ OVERLOAD 230V TO 24 V CONTROL TRANSFORMER

APPROXIMATE SHIPPING WEIGHT: 6000 LBS

RUN 1" CONDUIT & 3" CONDUIT WITH MIN. 14.5" RAD. BEND FROM POWER UNIT LOCATION TO PIT.

INSTALLER TO RUN 0.5" HYDRAULIC (2-WIRE) HOSE OR STAINLESS STEEL TUBING THRU 3" CONDUIT FROM POWER UNIT TO LIFT BASE.

ELECT. CONTR. TO RUN TRAVELLING ELECT. CORD THRU 1" CONDUIT TO JUNCTION BOX ON THE LIFT BASE.

DIMENSIONS SHOWN IN INCHES AND WEIGHTS SHOWN IN POUNDS UNLESS OTHERWISE NOTED

Advance Lifts, Inc. ANCE LIFTS 701 S. Kirk Road Phone : 630-584-9881 St. Charles, IL 60174 Fax : 630-584-6837				
		REVISIONS	BY	DATE
(Х	Х	Х	Х
Č.				
B470 DOCKLIFT B-				REV.