

**SPECIFICATIONS:** 

CAPACITY : 16,000 LBS MAX. LIFTING CAPACITY 12,800 LBS MAX. AXLE CAPACITY ENDS 11,200 LBS MAX. AXLE CAPACITY SIDES

PLATFORM : 96" WIDE X 144" LONG SAFETY TREAD DECK REMOVABLE STEEL GUARDRAILS 12" LONG X 72" WIDE HINGED STEEL BRIDGE ALL WITH CHAINS BEVEL TOE GUARDS SAFETY STRIPING

SPEED: 10 FPM

TRAVEL: 58" (FROM A 16.25" LOWERED HEIGHT)

LOWERED HEIGHT: 16 1/4"

POWER UNIT : 7 1/2 HP MOTOR 230V 60 Hz 3PH (REMOTE FROM LIFT)

CONTROL: UP-DOWN WEATHER-PROOF PUSHBUTTON STATION, PENDANT TYPE NEMA 1, 3, 3R, 4, 4X.

IN NEMA 12 ENCLOSURE : MAGNETIC STARTER,W/ OVERLOAD 230V TO 24 V CONTROL TRANSFORMER

APPROXIMATE SHIPPING WEIGHT: 7,200 LBS

- RUN 1" CONDUIT & 3" CONDUIT WITH MIN. 14.5" RAD. BEND FROM POWER UNIT LOCATION TO PIT.

INSTALLER TO RUN 0.5" HYDRAULIC (2-WIRE) HOSE OR STAINLESS STEEL TUBING THRU 3" CONDUIT FROM POWER UNIT TO LIFT BASE.

 $\mathsf{RD} \left\{ \begin{array}{l} \mathsf{ELECT. CONTR. TO RUN TRAVELLING} \\ \mathsf{ELECT. CORD THRU 1" CONDUIT} \\ \mathsf{TO JUNCTION BOX ON THE LIFT BASE.} \end{array} \right.$ 

DIMENSIONS SHOWN IN INCHES AND WEIGHTS SHOWN IN POUNDS UNLESS OTHERWISE NOTED

	NI	Advance Lifts, Inc.	e:630-	584-9881
Advance Liffs, Inc. ADVANCE LIFTS 701 S. Kirk Road Phone : 630-584-9881 St. Charles, IL 60174 Fax : 630-584-6837				
<sup>e</sup> NTS		REVISIONS	BY	DATE
XX/XX/XX	Х	X	Х	Х
XXX				
#XXX				
IAME XXXXX				
MODEL 3580 DOCKLIFT				REV.