ADVANCE LIFTS®

# Air Operated Tilters (ATI)

## When Durability Matters

**1 year parts and labor\10 year, 250,000 cycle structural warranty**

*The air operated tilters offer the advantage of requiring no electrical connections. They operate on shop air with a minimum of 60 psi. The angle of tilt may increase as the load is decreased, which automatically rotates the bin toward the operator as it is unloaded.*



## Special Features

- All units are equipped with motion dampening shock absorbers.
- All air springs have lifetime warranties.
- These units are fully primed and then receive a baked enamel finish.
- These units comply with all applicable ANSI codes.
- All units are equipped with safety maintenance locks.
- Standard controls are hand valves mounted on pipe stanchions. (Foot operated controls are optional).

## Specification Table for Air Operated Tilters

| Model | Capacity | Air Springs | Lowered Height | Tilt | Mininum Platform | Maximum Platform | Baseframe | Shipping Weight |
|---|---|---|---|---|---|---|---|---|
| ATI-135 | 1000 | 1 | 7-1/4 | 35 | 30 X 36 | 72 X 48 | 24 X 31-1/4* | 300 |
| ATI-235 | 2000 | 1 | 7-1/4 | 35 | 30 X 36 | 72 X 48 | 24 X 31-1/4* | 310 |
| ATI-335 | 3000 | 1 | 7-1/4 | 35 | 30 X 36 | 72 X 48 | 24 X 31-1/4* | 315 |
| ATI-435 | 4000 | 2 | 7-1/4 | 35 | 30 X 36 | 72 X 48 | 24 X 31-1/4* | 320 |
| ATI-535-D | 5000 | 2 | 7-1/4 | 35 | 36 X 36 | 72 X 48 | 36 X 31-1/4 | 425 |
| ATI-635-D | 6000 | 2 | 7-1/4 | 35 | 36 X 36 | 72 X 48 | 36 X 31-1/4 | 430 |

** Baseframe widths are increased from 24" to 36" for all platforms 60" wide or wider.*
*• All paired dimensions are width X length.*

**Phone: 800-843-3625 • Fax: 630-584-9405 • www.advancelifts.com**

©2020 Advance Lifts, Inc. All rights reserved.