ADVANCE LIFTS®

Air Operated Lift & Tilt (ATT) Series

When Durability Matters

1 year parts and labor\10 year, 250,000 cycle structural warranty

These units are designed to operate on shop air with no need for electricity.
Each model has been optimized for minimum weight and maximum value.



Special Features

- These units are equipped with the patented “Platform Centering Devices”, which doubles or triples lift life.
- These units are fully primed and finished with a baked enamel finish.
- All units are equipped with sealed ball bearing wheels.
- All shafts and axles are chrome plated 100,000 psi stressproof steel.
- All pivot bearings are lifetime lubricated.
- All tilters are equipped with (2) shock absorbers to smooth operations.
- These units are equipped with a pressure safety relief and a safety orifice speed control to regulate down speed in case of supply line hose rupture.

Specification Table For Air Operated Lift And Tilt Units

Model	Capacity	Platform Mininum	Platform Maximum	Lowered Height	Travel	Tilt	Ship Weight
ATT-1524	1500	30 x 48	48 x 48	15	24	35°	850
ATT-2524	2500	48 x 48	60 x 60	15	24	35°	1360
ATT-3524	3500	48 x 48	60 x 60	15	24	35°	1380
ATT-5024	5000	48 x 48	60 x 60	16-1/4	24	35°	1625
ATT-6024	6000	48 x 48	60 x 60	17-1/4	24	35°	1715

Phone: 800-843-3625 • Fax: 630-584-9405 • www.advancelifts.com

ADVANCE LIFTS®

©2020 Advance Lifts, Inc. All rights reserved.