ADVANCE LIFTS®

Air Operated Lift & Turn (ATR) Series

WHEN DURABILITY MATTERS

1 year parts and labor\10 year, 250,000 cycle structural warranty

These units are designed to operate on shop air with no need for electricity. Each model has been optimized for minimum weight and maximum value.



Special Features

- These units are equipped with the patented “Platform Centering Devices”, which doubles or triples lift life.
- These units are fully primed and finished with a baked enamel finish.
- All units are equipped with sealed ball bearing wheels.
- All shafts and axles are chrome plated 100,000 psi stressproof steel.
- All pivot bearings are lifetime lubricated.
- These units are equipped with a pressure safety relief and a safety orifice speed control to regulate down speed in case of supply line hose rupture.

Specification Table For Air Operated Lift and Turn Units

Model	Travel	Capacity	Platform Mininum	Platform Maximum	Base-frame	Lowered Height	Raised Height	Turn	Ship Weight
ATR-1524	24	1500	36 x 48	48 x 48	36 x 48	10-3/4	34-3/4	360º	690
ATR-2524	24	2500	48 x 48	60 x 60	48 x 48	10-3/4	34-3/4	360º	1210
ATR-3524	24	3500	48 x 48	60 x 60	48 x 48	10-3/4	34-3/4	360º	1220
ATR-5024	24	5000	48 x 48	60 x 60	48 x 48	12	36	360º	1375
ATR-6024	24	6000	48 x 48	60 x 60	48 x 48	13	37	360º	1450

Phone: 800-843-3625 • Fax: 630-584-9405 • www.advancelifts.com

©2020 Advance Lifts, Inc. All rights reserved.