ADVANCE LIFTS®

3000 Series Recessed Dock Lifts

These are our medium sized Disappearing Dock lifts. They are sized to handle pallet jacks, powered pallet jacks, straddle stackers and fork trucks. They are also used for dock to ground access.



Series 3000


Special Features

- All models are equipped with a hinged bridge with a pull back chain.
- All of the electrical controllers are Underwriters Laboratories approved assemblies.
- Each unit is washed with phosphoric acid, fully primed and then finished with baked enamel.
- All cylinders are machine grade with clear plastic return lines & internal mechanical stops.
- All pressure hoses are double wire braid with JIC fittings.
- Reservoirs are mild steel.
- These units conform to all applicable ANSI codes.


Feature Details




Power Unit



Cylinder



Double Wire Braid Hose



UL Listed Control Panel

Phone: 800-843-3625 • Fax: 630-584-9405 • www.advancelifts.com

©2022 Advance Lifts, Inc. All rights reserved.

Specification Table for 3000 Series Lifts

Model	Lift Capacity	Axle Cap. Ends	Axle Cap. Sides	Platform Size	Lowered Height	Travel	Speed FPM	Power Unit HP	Ship Weight
3100	8,000	6,150	4,250	6' X 8'	10″	58"	10	5	4,300
3110	8,000	6,150	4,250	6' X 9'	10″	58"	10	5	4,450
3120	8,000	6,150	4,250	6' X 10'	10″	58"	10	5	4,600
3130	8,000	6,150	4,250	7' X 8'	10″	58"	10	5	4,500
3140	8,000	6,150	4,250	7' X 9'	10″	58"	10	5	4,675
3150	8,000	6,150	4,250	7' X 10'	10″	58"	10	5	4,850
3160	8,000	6,150	4,250	8' X 8'	10″	58"	10	5	4,700
3170	8,000	6,150	4,250	8' X 9'	10″	58"	10	5	4,900
3180	8,000	6,150	4,250	8' X 10'	10″	58"	10	5	5,100
3200	8,000	6,500	5,000	6' X 8'	12″	58"	10	5	4,200
3210	8,000	6,500	5,000	6' X 9'	12″	58"	10	5	4,350
3220	8,000	6,500	5,000	6' X 10'	12″	58"	10	5	4,500
3230	8,000	6,500	5,000	7' X 8'	12″	58"	10	5	4,400
3240	8,000	6,500	5,000	7' X 9'	12″	58"	10	5	4,575
3250	8,000	6,500	5,000	7' X 10'	12″	58"	10	5	4,750
3260	8,000	6,500	5,000	8' X 8'	12″	58"	10	5	4,600
3270	8,000	6,500	5,000	8' X 9'	12″	58"	10	5	4,800
3280	8,000	6,500	5,000	8' X 10'	12″	58"	10	5	5,000
3300	10,000	8,000	5,000	6' X 8'	12″	58"	8	5	4,525
3310	10,000	8,000	5,000	6' X 9'	12"	58"	8	5	4,705
3320	10,000	8,000	5,000	6' X 10'	12"	58"	8	5	4,885
3330	10,000	8,000	5,000	7' X 8'	12"	58"	8	5	4,765
3340	10,000	8,000	5,000	7' X 9'	12"	58"	8	5	4,975
3350	10,000	8,000	5,000	7' X 10'	12″	58"	8	5	5,185
3360	10,000	8,000	5,000	8' X 8'	12"	58"	8	5	5,005
3370	10,000	8,000	5,000	8' X 9'	12"	58"	8	5	5,245
3380	10,000	8,000	5,000	8' X 10'	12"	58"	8	5	5,485

General:

These units are constructed with heavy wall tubing to maximize rigidity with minimum weight. The legs are “gibbed” to both the base frame and the platform to further enhance rigidity. If the intended use of this equipment includes small fork trucks, be sure to calculate the axle loading of the fork truck and compare it to the axle load limits in the table above.

©2022 Advance Lifts, Inc. All rights reserved.

Specification Table for 3000 Series Lifts

Model	Lift Capacity	Axle Cap. Ends	Axle Cap. Sides	Platform Size	Lowered Height	Travel	Speed FPM	Power Unit HP	Ship Weight
Fork Lift Capacity 3400 – 3600									
3400	12,000	9,600	8,400	6' x 10'	15"	58"	7	5	5,500
3410	12,000	9,600	8,400	6' x 11'	15"	58"	7	5	5,700
3420	12,000	9,600	8,400	6' x 12'	15"	58"	7	5	5,900
3430	12,000	9,600	8,400	7' x 10'	15"	58"	7	5	5,800
3440	12,000	9,600	8,400	7' x 11'	15"	58"	7	5	6,050
3450	12,000	9,600	8,400	7' x 12'	15"	58"	7	5	6,300
3460	12,000	9,600	8,400	8' x 10'	15"	58"	7	5	6,300
3470	12,000	9,600	8,400	8' x 11'	15"	58"	7	5	6,600
3480	12,000	9,600	8,400	8' x 12'	15"	58"	7	5	6,900
3500	16,000	12,800	11,200	6' x 10'	16-1/4"	58"	10	7-1/2	5,800
3510	16,000	12,800	11,200	6' x 11'	16-1/4"	58"	10	7-1/2	6,000
3520	16,000	12,800	11,200	6' x 12'	16-1/4"	58"	10	7-1/2	6,200
3530	16,000	12,800	11,200	7' x 10'	16-1/4"	58"	10	7-1/2	6,100
3540	16,000	12,800	11,200	7' x 11'	16-1/4"	58"	10	7-1/2	6,350
3550	16,000	12,800	11,200	7' x 12'	16-1/4"	58"	10	7-1/2	6,600
3560	16,000	12,800	11,200	8' x 10'	16-1/4"	58"	10	7-1/2	6,600
3570	16,000	12,800	11,200	8' x 11'	16-1/4"	58"	10	7-1/2	6,900
3580	16,000	12,800	11,200	8' x 12'	16-1/4"	58"	10	7-1/2	7,200
3600	20,000	16,000	14,000	6' x 10'	17-1/2"	58"	8	7-1/2	6,900
3610	20,000	16,000	14,000	6' x 11'	17-1/2"	58"	8	7-1/2	7,300
3620	20,000	16,000	14,000	6' x 12'	17-1/2"	58"	8	7-1/2	7,900
3630	20,000	16,000	14,000	7' x 10'	17-1/2"	58"	8	7-1/2	7,000
3640	20,000	16,000	14,000	7' x 11'	17-1/2"	58"	8	7-1/2	7,400
3650	20,000	16,000	14,000	7' x 12'	17-1/2"	58"	8	7-1/2	8,000
3660	20,000	16,000	14,000	8' x 10'	17-1/2"	58"	8	7-1/2	8,000
3670	20,000	16,000	14,000	8' x 11'	17-1/2"	58"	8	7-1/2	7,800
3680	20,000	16,000	14,000	8' x 12'	17-1/2"	58"	8	7-1/2	8,100

General:

These units are constructed with heavy wall tubing to maximize rigidity with minimum weight. The legs are “gibbed” to both the base frame and the platform to further enhance rigidity. If the intended use of this equipment includes small fork trucks, be sure to calculate the axle loading of the fork truck and compare it to the axle load limits in the table above.

©2022 Advance Lifts, Inc. All rights reserved.