

MODEL 1055 TOP OF GROUND DOCK LIFT

2 Year Parts & Labor/10 Year Structural Warranty

These are Instant Docks that simply require positioning and plugging into a power receptacle and they are ready to go to work. They were designed for use with light equipment such as hand carts, 4 wheels carts and pallet jacks.

Capacity: 5,000 lbs

Axle Capacity Bridge Ends: 2,000 lbs.

Platform Size: 6 x 6 ft.

Overall Size: 76 x 92 in.

Lowered Height: 5.25 in.

Bridge Size: 18 x 60 in.

Chock/Ramp Size: 30 x 60 in.

2 HP Motor

Approx. 8 FPM

53" Travel

Shipping Weight: 2,500 lbs.

**ISO 9001:2015
Certified**



Model# 1055

SPECIAL FEATURES & BENEFITS

- ▶ All models are equipped with a hinged bridge equipped with a pull back chain.
- ▶ All models have a combination approach ramp, wheel chock.
- ▶ All of the electrical controllers are Underwriters Laboratories approved assemblies.
- ▶ Each unit is washed with phosphoric acid, fully primed and then finished with baked enamel.
- ▶ All cylinders are machine grade with clear plastic return lines.
- ▶ All pressure hoses are double wire braid with JIC fittings.
- ▶ These units conform to all applicable ANSI codes.

CLICK HERE FOR: [Drawing](#) [Pad Diagram](#) [Specifications](#) [Optional Accessories](#)

FEATURE DETAILS




▶ *Power Unit
w/Controller*



▶ *Cylinder*



▶ *Double Wire
Braid Hose*



▶ *Combination Wheel
Chock/Ramp*