

MODEL 612812 TOP OF GROUND DOCK LIFT

2 Year Parts & Labor/10 Year Structural Warranty

These are Instant Docks that simply require lagging into position and plugging into a power receptacle and they are ready to go to work. No pit work is required.

**ISO 9001:2015
Certified**



Capacity: 12,000 lbs.
Axle Capacity Ends: 9,600 lbs.
Platform Size: 8 x 12 ft.
Overall Size w/Ramp: 112 x 189 in.
Lowered Height: 6 in.
Bridge Size: 18 x 72 in.
Ramp Size: 42 x 78 in.
7.5 HP Motor
Approx. 11 FPM
52" Travel
Shipping Weight: 5,775 lbs.




Model# 612812

SPECIAL FEATURES & BENEFITS


- ▶ All models are equipped with a hinged bridge equipped with a pull back chain.
- ▶ All models have an approach ramp.
- ▶ All of the electrical controllers are Underwriters Laboratories approved assemblies.
- ▶ Each unit is washed with phosphoric acid, fully primed and then finished with baked enamel.
- ▶ All cylinders are machine grade with clear plastic return lines.
- ▶ All pressure hoses are double wire braid with JIC fittings.
- ▶ These units conform to all applicable ANSI codes.

CLICK HERE FOR: [Drawing PDF](#) [DXF](#) [Pad Diagram](#) [Specifications](#) [Optional Accessories](#)


FEATURE DETAILS




▶ *Power Unit
w/Controller*



▶ *UL Listed Control
Panel*



▶ *Double Wire
Braid Hose*



▶ *Combination Wheel
Chock/Ramp*