

# MODEL 65610 TOP OF GROUND DOCK LIFT

**2 Year Parts & Labor/10 Year Structural Warranty**

*These are Instant Docks that simply require lagging into position and plugging into a power receptacle and they are ready to go to work. No pit work is required.*

**ISO 9001:2015  
Certified**



Capacity: 5,500 lbs.  
Axle Capacity Ends: 2,750 lbs.  
Platform Size: 6 x 10 ft.  
Overall Size w/Ramp: 81 x 153 in.  
Lowered Height: 5 in.  
Bridge Size: 18 x 60 in.  
Ramp Size: 30 x 60 in.  
5 HP Motor  
Approx. 13 FPM  
53" Travel  
Shipping Weight: 3,340 lbs.




*Model# 65610*

## SPECIAL FEATURES & BENEFITS


- ▶ All models are equipped with a hinged bridge equipped with a pull back chain.
- ▶ All models have an approach ramp.
- ▶ All of the electrical controllers are Underwriters Laboratories approved assemblies.
- ▶ Each unit is washed with phosphoric acid, fully primed and then finished with baked enamel.
- ▶ All cylinders are machine grade with clear plastic return lines.
- ▶ All pressure hoses are double wire braid with JIC fittings.
- ▶ These units conform to all applicable ANSI codes.

**CLICK HERE FOR:** [Drawing PDF](#) [DXF](#) [Pad Diagram](#) [Specifications](#) [Optional Accessories](#)


## FEATURE DETAILS




▶ *Power Unit  
w/Controller*



▶ *UL Listed Control  
Panel*



▶ *Double Wire  
Braid Hose*



▶ *Combination Wheel  
Chock/Ramp*