

MODEL ATT-2524 AIR OPERATED LIFT AND TILT

10 Year/250,000 Cycle Warranty

These units are designed to operate on shop air with no need for electricity. Each model has been optimized for minimum weight and maximum value.

ISO 9001:2015 Certified





Capacity: 2,500 lbs. Min. Platform Size: 48 x 48 in. Max. Platform Size: 60 x 60 in. Lowered Height: 15 in. Travel: 24 in. Raised Height: 39 in. Degree of Tilt: 35 Shipping Weight: 1,360 lbs.



2,500 lb. Capacity - 24 in. Travel

SPECIAL FEATURES & BENEFITS

- > These units are equipped with the patented "Platform Centering Devices", which doubles or triples lift life.
- These units are fully primed and finished with a baked enamel finish.
- All units are equipped with sealed ball bearing wheels.
- All shafts and axles are chrome plated 100,000 psi stressproof steel.
- All pivot bearings are lifetime lubricated.
- All tilters are equipped with (2) shock absorbers to smooth operations.
- These units are equipped with a pressure safety relief and a safety orifice speed control to regulate down speed in case of supply line hose rupture.

CLICK HERE FOR: Optional Accessories



Phone: 800-843-3625 • Fax: 630-584-9405 • www.advancelifts.com