

MODEL BTS-4 BIN TILTER - STRADDLE

10 Year/250,000 Cycle Warranty

These units are designed to reduce reaching and bending into parts containers. There are models suitable for palletized loads, carts and stacker bins.

**ISO 9001:2015
Certified**



Capacity: 4,000 lb.
Degree of Tilt: 87
Fork Length: 40 in.
Fork Height: 3.5 in.
Overall Fork Spacing: 26 in.
Inside Straddle: 50.5 in.
Overall Width: 57.5 in.
Overall Length: 55.5 in.
Overall Height: 35.25 in.
Tilt Speed: 25 sec.
Shipping Weight: 750 lbs



4,000 lb. Capacity - 87 Degrees of Tilt


SPECIAL FEATURES & BENEFITS

- ▶ All models have hydraulic return lines on the cylinders to preclude oil weepage.
- ▶ BT & BTS portable models are equipped with a 12 volt DC deep cycle battery power unit.
- ▶ All battery operated units are equipped with built in battery chargers.
- ▶ BTP non-portable pan tilters are equipped with 1HP AC 110 Volt motors.
- ▶ Portable units have “step down set”, “step down release” floor locks for ease of operation.
- ▶ Portable units have ankle protection around the portability casters for added safety.
- ▶ BT models have a backrest extension option to support extra wide containers.
- ▶ All units have warning light and audio warning options available.

CLICK HERE FOR: [Optional Accessories](#)



BTP-2



***BT-2 w/ optional
hinged backrest extensions***