

MODEL P-2560 SCISSORS LIFT - LIFT TABLE

10 Year/250,000 Cycle Warranty

The P-Series lifts are our most popular series as they fit a wide array of manufacturing applications.

**ISO 9001:2015
Certified**



Min. Platform Size: 24 x 84 in.
Max. Platform Size: 48 x 120 in.
Max. End Load Capacity 2,500 lbs.
Max. Side Load Capacity: 2,500 lbs.
Baseframe Size: 24 x 84 in.
Lowered Height: 10 in.
Raised Height: 70 in.
Approx. Speed Up: 28 sec.
Internal Motor: 2 HP
Shipping Weight: 1,000 lbs.




2,500 lb. Capacity - 60 in. Travel

SPECIAL FEATURES & BENEFITS

- ▶ These units are equipped with the patented “Platform Centering Devices”, which doubles or triples lift life.
- ▶ All of the controllers are Underwriter Laboratory listed assemblies.
- ▶ These units are fully primed and finished with a baked enamel finish.
- ▶ The cylinders are machine grade with clear plastic return lines.
- ▶ All pressure hoses are double wire braid with JIC fittings.
- ▶ The reservoirs are mild steel.
- ▶ These units conform to all applicable ANSI codes.

CLICK HERE FOR: [Optional Accessories](#)

FEATURE DETAILS



▶ **Platform Centering Device**



▶ **Machine Grade Cylinder**



▶ **Double Wire Braid Hose**



▶ **Power Unit**