

MODEL PAC-200 PACKAGE LIFT

5 Year Structural Warranty
1 Year Electrical/Hydraulic

These VRC's are small free standing devices designed for light loads and relatively fast movement from ground level to mezzanine level. They are rugged four (4) post construction that is fully assembled at the factory and can be shipped as 1 piece tilt up installation or as two (2) or three (3) piece stackable sections for quick and easy installation. The doors are typically set to open 30" above grade at each level, but can be set to open at grade level at upper landings and 3" above grade at the lower level. These units are well suited for automated operations.

**ISO 9001:2015
Certified**



Min. Platform Size: 24 x 24 in.
Max. Platform Size: 36 x 36 in.
Lowered Height: 30 std/3 min
Overall Height: 80" + Travel
Overall Min. Width: 33 in.
Overall Min. Depth: 36 in.
Travel Max: 24 ft.
Speed: 30 fpm.
Horse Power: 1/2 HP



200 lb. Capacity - 24' Travel

SPECIAL FEATURES & BENEFITS

- ▶ All of our controllers are assembled in our UL listed panel shop
- ▶ These units conform to all applicable ANSI and ASME codes
- ▶ Motors are equipped with integral brake locks
- ▶ Units are equipped with double chains
- ▶ All units have flattened expanded enclosures attached at the factory
- ▶ Platforms have dual surface guides in all four (4) corners
- ▶ Call-send-stop buttons mounted at each level
- ▶ Platforms are equipped with load retention bars on all four (4) sides
- ▶ Power drive units mounted in the top of each unit, other configurations are available