

# MODEL UHC-6032 ULTRA HIGH CYCLE SERIES LIFT


**10 Year/3,000,000 Cycle Warranty**

*When heavy loads need to be moved quickly, precisely and with consistent repeatability and/or a lift is expected to operate in an application which will exceed millions of cycles, an ultra high cycle lift should be considered. With the rigid structure of our UHC lift, very accurate positioning can be obtained with a standard positioning accuracy of +/- 1/4" and an optional positioning accuracy of +/- .030". Our Ultra High Cycle lifts offer not only accuracy and durability, but lower maintenance costs, less down time, reduced or eliminated lift replacement costs and flexible installation requirements which all add up to greater value in demanding applications.*

**ISO 9001:2015  
Certified**



Min. Platform Size: 36 x 50 in.  
 Max. Platform Size: 72 x 90 in.  
 Max. End Capacity: 6,000 lbs.  
 Loading Side Capacity: 6,000 lbs.  
 Baseframe Size: 36 x 50 in.  
 Lowered Height: 11.25 in.  
 Raised Height: 43.25 in.  
 Approx. Speed Up: 4 sec.  
 External Motor: 10 HP  
 Shipping Weight: 1,900 lbs.




**6,000 lb. Capacity - 32 in. Travel**

## SPECIAL FEATURES & BENEFITS

- ▶ Warranted for 3,000,000 cycles.
- ▶ All units equipped with linear displacement transducers.
- ▶ Underwriter Laboratory listed electrical controllers with smart relays.
- ▶ Solid lubricant filled slides in place of roller wheels.
- ▶ Custom designated valve block to provide cylinder isolation and multi-speed operation.
- ▶ Continuous running power units with oil filter.
- ▶ Machine grade single acting cylinders with flooded rods.
- ▶ Each unit is washed with phosphoric acid, fully primed & finished with a baked enamel.

**CLICK HERE FOR: [Optional Accessories](#)**

## FEATURE DETAILS




▶ **Live Swivel  
Hydraulic Connection**



▶ **Hinged Maintenance  
Device**



▶ **Replaceable Roller  
Wear Strip**



▶ **Multi-Speed  
Valve Block**