

## MODEL 610812 TOP OF GROUND DOCK LIFT

## 2 Year Parts & Labor/10 Year Structural Warranty

These are Instant Docks that simply require lagging into position and plugging into a power receptacle and they are ready to go to work. No pit work is required.

ISO 9001:2015 Certified





Axle Capacity Ends: 8,000 lbs.
Platform Size: 8 x 12 ft.
Overall Size w/Ramp: 112 x 189 in.
Lowered Height: 6 in.
Bridge Size: 18 x 72 in.
Ramp Size: 42 x 78 in.
7.5 HP Motor
Approx. 11 FPM
52" Travel

Capacity: 10,000 lbs.



## Special Features & Benefits

- All models are equipped with a hinged bridge equipped with a pull back chain.
- All models have an approach ramp.
- ▶ All of the electrical controllers are Underwriters Laboratories approved assemblies.

Shipping Weight: 5,775 lbs.

- Each unit is washed with phosphoric acid, fully primed and then finished with baked enamel.
- All cylinders are machine grade with clear plastic return lines.
- All pressure hoses are double wire braid with JIC fittings.
- ▶ These units conform to all applicable ANSI codes.

**CLICK HERE FOR:** Drawing PDF DXF Pad Diagram Specifications Optional Accessories

## FEATURE DETAILS




► Power Unit w/Controller



► UL Listed Control
Panel



Double Wire Braid Hose



Combination Wheel Chock/Ramp



Phone: 800-843-3625 • Fax: 630-584-9405 • www.advancelifts.com