

MODEL HC-2518 HIGH CYCLE SERIES LIFT

10 Year/1,000,000 Cycle Warranty

These lifts were designed for automated machine feeding or off loading applications that will accumulate cycles very quickly. Standard lift speeds start out twice as fast as our P series units and can be modified to customer needs approaching the 40 feet per minute speed of our UHC lifts. This high cycle unit is a clean and simple design, but it is still feature rich and unmatched by any competitor.

**ISO 9001:2015
Certified**



Min. Platform Size: 36 x 36 in.
Max. Platform Size: 48 x 48 in.
Max. End Capacity: 2,500 lbs.
Loading Side Capacity: 2,500 lbs.
Baseframe Size: 36 x 36 in.
Lowered Height: 9.5 in.
Raised Height: 27.5 in.
Approx. Speed Up: 11.5 FPM
External Motor: 2 HP
Shipping Weight: 1,000 lbs.




2,500 lb. Capacity - 18 in. Travel

SPECIAL FEATURES & BENEFITS

- ▶ Warranted for 1,000,000 cycles.
- ▶ Soft start - soft stop operating speed.
- ▶ Underwriter Laboratory listed electrical controllers with smart relays.
- ▶ Patented platform centering devices.
- ▶ Custom designed valve block to provide cylinder isolation and multi-speed operation.
- ▶ Continuous running power units with oil filter.
- ▶ Machine grade single acting cylinders with flooded rods.
- ▶ Double wire braid hoses with JIC fittings.
- ▶ Each unit is washed with phosphoric acid, fully primed & finished with a baked enamel.

CLICK HERE FOR: [Optional Accessories](#)

FEATURE DETAILS




▶ **Live Swivel
Hydraulic Connection**



▶ **Hinged Maintenance
Device**



▶ **Replaceable Roller
Wear Strip**



▶ **Multi-Speed
Valve Block**