

# MODEL HC-4031 HIGH CYCLE SERIES LIFT

**10 Year/1,000,000 Cycle Warranty**

*These lifts were designed for automated machine feeding or off loading applications that will accumulate cycles very quickly. Standard lift speeds start out twice as fast as our P series units and can be modified to customer needs approaching the 40 feet per minute speed of our UHC lifts. This high cycle unit is a clean and simple design, but it is still feature rich and unmatched by any competitor.*

**ISO 9001:2015  
Certified**



Min. Platform Size: 36 x 48 in.  
Max. Platform Size: 48 x 60 in.  
Max. End Capacity: 4,000 lbs.  
Loading Side Capacity: 4,000 lbs.  
Baseframe Size: 36 x 48 in.  
Lowered Height: 10 in.  
Raised Height: 41 in.  
Approx. Speed Up: 11.5 FPM  
External Motor: 2 HP  
Shipping Weight: 1,650 lbs.




**4,000 lb. Capacity - 31 in. Travel**

## SPECIAL FEATURES & BENEFITS

- ▶ Warranted for 1,000,000 cycles.
- ▶ Soft start - soft stop operating speed.
- ▶ Underwriter Laboratory listed electrical controllers with smart relays.
- ▶ Patented platform centering devices.
- ▶ Custom designed valve block to provide cylinder isolation and multi-speed operation.
- ▶ Continuous running power units with oil filter.
- ▶ Machine grade single acting cylinders with flooded rods.
- ▶ Double wire braid hoses with JIC fittings.
- ▶ Each unit is washed with phosphoric acid, fully primed & finished with a baked enamel.

**CLICK HERE FOR: [Optional Accessories](#)**

## FEATURE DETAILS




▶ **Live Swivel  
Hydraulic Connection**



▶ **Hinged Maintenance  
Device**



▶ **Replaceable Roller  
Wear Strip**



▶ **Multi-Speed  
Valve Block**