

MODEL TM-400 STANDARD DUTY NON-POWERED, TURNTABLE

10 Year/250,000 Cycle Warranty

Turntables are used for positioning jobs where heavy duty loads must be rotated on a regular basis. There are two basic types of standard duty turntables, non-powered and powered. Turntables are available in low profile and high profile configurations.

ISO 9001:2015 Certified



Capacity: 4,000 lbs. Edge Load Max: 100 lbs. Minimum Platform: 24 x 24 in. Maximum Platform: 48 x 48 in. Height: 3.5 in. Roller Radius: 10 Weight: 450 lbs.



4,000 lb. Capacity



Standard platform is square,

circular is available upon request.

SPECIAL FEATURES & BENEFITS

- Lower cost than powered turntables.
- These units are manually rotated.
- These units can be rotated in either direction.
- All non-powered turntables are low profile.
- > Standard platforms are rectangular and round platforms are optional on all models except TML.
- **•** Rotational limits can be provided via optional detents, locking pins, and hard stops.
- > TM platforms are supported by lifetime lubricated roller bearing cam followers.
- > TML platforms are supported by lifetime lubricated ball bearing roller.
- > Platforms rotate around a lifetime-lubricated kingpin bearing.

CLICK HERE FOR: Optional Accessories

FEATURE DETAILS

OPTIONAL ROTATIONAL LIMITS FOR <u>MANUAL</u> TURNTABLES: **D**ETENTS, LOCKING PINS AND HARD STOPS



▶ Detent



Locking pin





Phone: 800-843-3625 • Fax: 630-584-9405 • www.advancelifts.com

