

MODEL TPH-1005 STANDARD DUTY POWERED, HIGH PROFILE TURNTABLE

10 Year/250,000 Cycle Warranty

Turntables are used for positioning jobs where heavy duty loads must be rotated on a regular basis. There are two basic types of standard duty turntables, non-powered and powered. Turntables are available in low profile and high profile configurations.

ISO 9001:2015 Certified

Edge Load Max: 500 lbs.

Capacity: 10.000 lbs.

Minimum Platform: 49 x 49 in.

Max Platform Size: 60 x 60 in.


Height: 10 in.

Roller Radius: 15

Speed: 0-3.5 rpm

Motor: 1 HP

Weight: 1,075 lbs.



10,000 lb. Capacity





Standard platform is square, circular is available upon request.

SPECIAL FEATURES & BENEFITS

- Used where more frequent turning is required.
- Used where rotational effort would be too high in a non-powered turntable.
- Standard turntables use DC motors and drives; AC motors and drives are optional.
- Standard rotation is clockwise only.
- Optional bi-directional rotation (clockwise & counterclockwise) requires an AC motor and drive.
- Platforms rotate on a lifetime-lubricated kingpin bearing.
- ▶ Platform travel can be limited by use of optional limit switch $(+/-3^{\circ}$ accuracy).
- Powered turntables are available in low profile and high profile configurations.
 - High profile powered turntables:
 - Use for powered applications where low platform height is not important.
 - Standard platforms are rectangular and round platforms are optional.
 - Drive motor is located under the platform.
 - Platforms are supported by inverted casters with tapered roller bearings or cam followers.

CLICK HERE FOR: Optional Accessories

FEATURE DETAILS

OPTIONAL ROTATIONAL LIMITS FOR POWERED TURNTABLES: LIMIT SWITCHES, PROXIMITY SENSORS, PRECISION CONTROL PLC



▶ Limit switch



Lifetime lubricated roller bearing wheel style of unit



▶ Programmable logic controller



